

**FEATURES:**

- 4-20 mA with 1 μ A resolution
- Basic Accuracy 0.025% + 5 μ A
- Auto-Ramp and Easy Step Functions
- 1-100% Input
- 0-20mA, 0-24mA Selectable
- 0-24V Output

ELECTRICAL SPECIFICATIONS:

RANGE	RESOLUTION	Accuracy
0-4mA	0.001mA	$\pm 0.025\% \pm 10\mu A$
4-20mA	0.001mA	$\pm 0.025\% \pm 5\mu A$
20-24mA	0.001mA	$\pm 0.025\% \pm 5\mu A$
0-4V	0.001V	$\pm 0.05\% \pm 10mV$
4-20V	0.001V	$\pm 0.05\% \pm 5mV$
20-24V	0.001V	$\pm 0.05\% \pm 5mV$

GENERAL SPECIFICATIONS:

Battery Type: 9V Alkaline Battery (External Power Input 9-15V)

Display: 4+5 Digits

Operating Temperature: 0 to 50°C (32 to 122°F)

Operating Humidity: Less than 85% relative

Storage Temperature: -20 to 60°C (-4 to 140°F)

Dimension: 88×168×26mm

Weight: 330g

Accessories: Carrying case, Users Manual, 6×1.5V AA batteries, External Battery Pack, Alligator clip.

eximus[®] cs S.R.O.

IČO: 25322311, DIČ: CZ25322311, www.eximus.cz, eximus@eximus.cz

Čapkova 22
678 01 Blansko
Česká republika
Tel.: +420 - 516 432 999
+420 - 516 432 680
+420 - 516 433 701
Fax: +420 - 516 432 999